


FPGA Configuration PROM Parallel/Serial 1M-bit 2.5V/3.3V 20-Pin PLCC



Images are for reference only

[Inquiry](#)

Manufacturer:	AMD Xilinx, Inc
Package/Case:	PLCC20
Product Type:	Programmable Logic ICs
Lifecycle:	Obsolete

General Description

Xilinx introduces the XC18V00 series of in-system programmable configuration PROMs (Figure 1). Devices in this 3.3V family include a 4-megabit, a 2-megabit, a 1-megabit, and a 512-kilobit PROM that provide an easy-to-use, cost-effective method for reprogramming and storing Xilinx FPGA configuration bitstreams.

When the FPGA is in Master Serial mode, it generates a configuration clock that drives the PROM. A short access time after CE and OE are enabled, data is available on the PROM DATA (D0) pin that is connected to the FPGA DIN pin. New data is available a short access time after each rising clock edge. The FPGA generates the appropriate number of clock pulses to complete the configuration. When the FPGA is in Slave Serial mode, the PROM and the FPGA are clocked by an external clock.

When the FPGA is in Master SelectMAP mode, the FPGA generates a configuration clock that drives the PROM. When the FPGA is in Slave Parallel or Slave SelectMAP mode, an external oscillator generates the configuration clock that drives the PROM and the FPGA. After CE and OE are enabled, data is available on the PROM's DATA (D0-D7) pins. New data is available a short access time after each rising clock edge. The data is clocked into the FPGA on the following rising edge of the CCLK. A free-running oscillator can be used in the Slave Parallel or Slave SelectMAP modes.

Multiple devices can be cascaded by using the CEO output to drive the CE input of the following device. The clock inputs and the DATA outputs of all PROMs in this chain are interconnected. All devices are compatible and can be cascaded with other members of the family or with the XC17V00 one-time programmable serial PROM family.

Recommended For You

[XC128XFT64C](#)

AMD Xilinx, Inc
BGA

[XC18V04VQ41](#)

AMD Xilinx, Inc
QFP

[XC17128EPD8I](#)

AMD Xilinx, Inc
DIP8

[XC1765ELSO8C](#)

AMD Xilinx, Inc
SOP8

[XC18V04VQ44C](#)

AMD Xilinx, Inc
QFP44

[XC18V01SO20C](#)

AMD Xilinx, Inc
SOP20

XC18V04VQG44C

AMD Xilinx, Inc

QFP

XCF32PVOG48C

AMD Xilinx, Inc

TSOP48

XC18V01PCG20C

AMD Xilinx, Inc

PLCC20

XCF04SVO20C

AMD Xilinx, Inc

TSSOP20

XC2C256-7CPG132I

AMD Xilinx, Inc

BGA132

XCF04SVOG20C

AMD Xilinx, Inc

TSSOP20

XCF08PFS48C

AMD Xilinx, Inc

BGA

XC18V01VQ44C

AMD Xilinx, Inc

TQFP44

XC1765EPD8C

AMD Xilinx, Inc

DIP8