

TVS Diode Single Uni-Dir 30.8V 1.5KW Automotive 2-Pin SMC T/R

Manufacturer: <u>STMicroelectronics, Inc</u>

Package/Case: SMC

Product Type: Thyristors

Lifecycle: Active Images are for reference only

Inquiry

General Description

The SM15TY series are designed to protect sensitive automotive circuits against surges defined in ISO 7637-2 and against electrostatic discharges according to ISO 10605. The Planar technology makes it compatible with high-end circuits where low leakage current and high junction temperature are required to provide long term reliability and stability.

Key Features

AEC-Q101 qualified

Peak pulse power: 1500 W (10/1000 μs) and 10 kW (8/20 μs)

Stand-off voltage range from 5.8 V to 70 V

Unidirectional and bidirectional types

Low leakage current: 0.2 μA at 25 °C and 1 μA at 85 °C

Operating Tj max: 150 °C

High power capability at Tj max.: up to 1250 W (10/1000 μs)

Lead finishing: matte tin plating

Recommended For You

SMI5T68A SMAJ24A-TR SM2T6V8A

STMicroelectronics, Inc STMicroelectronics, Inc STMicroelectronics, Inc

DO-214AB SMA DO-216AA

SM30T33AY SM6T27AY SM6T33CAY

STMicroelectronics, Inc STMicroelectronics, Inc STMicroelectronics, Inc

SMC SMB SMB

SM6T36AY SM0T30CAY SM0T39CAY

STMicroelectronics, Inc STMicroelectronics, Inc STMicroelectronics, Inc

SMB SMC DO-214AB

SMB0T35CAY SM6T36CAY SM6T27CAY

STMicroelectronics, Inc STMicroelectronics, Inc STMicroelectronics, Inc

SMC SMB SMB

SM15T36AY SM6T30CAY SM15T36CAY

STMicroelectronics, Inc STMicroelectronics, Inc STMicroelectronics, Inc

SMC SMB SMC